



| | B430 |
|-----------------------------------|---|
| Model | B430 |
| Product Type | Zoom Bullet |
| Maximum Resolution | 3MP |
| Application Environment | Outdoor |
| Image Sensor | Progressive Scan CMOS |
| Day / Night | Yes |
| Superior Low Light Sensitivity | Yes |
| Minimum Illumination | Color: 0.1 lux, B/W: 0 lux (IR LED on) at F1.6 |
| Mechanical IR Cut Filter | Yes |
| IR LED | Yes, Adaptive IR (Object & Zoom Adaptive IR) |
| IR Working Distance | 40m |
| Lens | Zoom, f4.5-135mm / F1.6-4.4, DC iris, Auto focus |
| Zoom Ratio | 30x optical |
| Lens Mount | Board mount |
| Horizontal Viewing Angle | 59.8°-2.34° |
| Compression | H.264 High Profile, MJPEG |
| Maximum Frame Rate vs. Resolution | 15 fps at 4000 x 3000 24 fps at 4092 x 2160 30 fps at 2592 x 1944 30 fps at 2048 x 1536 120 fps at 1920 x 1080 120 fps at 1280 x 720 120 fps at 640 x 480 120 fps at 320 x 240 |
| Horizontal Resolution (TV lines) | 2150 TVL |
| Image Orientation | Rotation (0°, 90°) |
| Multi-Streaming | Dual streams |
| Wide Dynamic Range | Advanced WDR (80 dB) |
| Digital Noise Reduction | 2D+3D DNR |
| Digital Image Stabilizer | Digital Image Stabilizer |
| S/N Ratio | 56 dB |
| Audio | 2-way (Line-in, Line-out) |
| Network Protocol & Service | TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour |
| Pan, Tilt or Zoom protocol | Visca, Pelco-D, Pelco-P |

| | |
|--|--|
| Network Connector | RJ-45 |
| Digital Input/Output | 1/1 |
| Local Storage | MicroSDHC/MicroSDXC memory card slot (card not included) |
| Power Source | DC 12V; PoE Class 3 |
| Environmental Casing | Weatherproof (IP67); Vandal proof metal casing (IK10) |
| Bundled Accessories | Integrated Bracket |
| Mount Type | Wall, Ceiling, Pole, Gang Box |
| Built-in Analytics | Face Detection, Motion Detection, Tamper, People Counting |
| Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server) | Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection |
| Client PC Operating System | Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP |
| PC Web Browser | IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime |
| ONMF Compliant | Yes |
| Heater | Yes |
| Fan | No |
| Starting Temperature | -40°C ~ 50°C (-40°F ~ 122°F) within 30 minutes |
| Operating Temperature | -40°C ~ 50°C (-40°F ~ 122°F) |
| Approvals | CE, FCC, IP67, NEMA4X, IK10 (metal casing) |
| Warranty | 3 Years |
| Product Availability | ACTi : 2015.02.13 Distributor : 2015.03.13 |
| MSRP (local, reference only) | Please contact our sales |