

| | E213 |
|-----------------------------------|--|
| Model | E213 |
| Product Type | Zoom Box |
| Maximum Resolution | 5MP |
| Application Environment | Indoor/Outdoor |
| Image Sensor | Progressive Scan CMOS |
| Day/ Night | Yes |
| Superior Low Light Sensitivity | No |
| Mnimum Illumination | Color: 0.1 lux, B/W: 0.05 lux at F2.8 |
| Mechanical IR Cut Filter | Yes |
| IRLED | No |
| Lens | Zoom, f4.96-49.6mm / F2.8-3.5, Fixed iris, Auto focus |
| Zoom Ratio | 10x optical |
| Lens Mount | Board mount |
| Horizontal Mewing Angle | 63°-6.3° |
| Compression | H.264 High Profile, MJPEG |
| Maximum Frame Rate vs. Resolution | 15 fps at 2592 x 1944 15 fps at 2048 x 1536 30 fps at 1920 x 1080 30 fps at 1280 x 720 30 fps at 800 x 600 30 fps at 640 x 480 15 fps at 320 x 240 |
| Horizontal Resolution (TV lines) | 1350 TVL |
| Multi-Streaming | Dual streams |
| Wide Dynamic Range | Basic WDR (74 dB) |
| Digital Noise Reduction | DNR |
| S/N Ratio | 52 dB |
| Audio | 2-way (Line-in, Line-out) |
| Network Protocol & Service | TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour |
| Pan, Tilt or Zoom protocol | Visca, Pelco-D, Pelco-P |
| Network Connector | RJ-45 |
| Digital Input/Output | 1/1 |
| Serial Port | RS-485, RS-422 |

| Local Storage | McroSDHC/McroSDXC memory card slot (card not included) |
|--|---|
| Power Source | PoE Class 2 |
| Environmental Casing | Optional housing (IP66) |
| Bundled Accessories | No |
| Mount Type | Wall, Ceiling, Corner, Pole |
| Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server) | Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Mssing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection |
| Client PC Operating System | Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP |
| PC Web Browser | IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime |
| ONVIF Compliant | Yes |
| Starting Temperature | -10°C ~ 50°C (14°F ~ 122°F) |
| Operating Temperature | -10°C ~50°C (14°F ~ 122°F) |
| Approvals | CE, FCC |
| Warranty | 3 Years |
| Product Availability | ACTi : 2014.11.28 Distributor : 2014.12.28 |
| MSRP (local, reference only) | Log-in required |