



	E816
Model	E816
Product Type	Zoom Dome
Maximum Resolution	10MP
Application Environment	Outdoor
Image Sensor	Progressive Scan CMOS
Day / Night	Yes
Superior Low Light Sensitivity	No
Minimum Illumination	Color: 0.1 lux, B/W: 0 lux (IR LED on) at F1.4
Mechanical IR Cut Filter	Yes
IR LED	Yes, Adaptive IR (Object & Zoom Adaptive IR)
IR Working Distance	30m
Lens	Zoom, f3.1-13.3mm / F1.4-4.0, P-iris, Auto focus
Zoom Ratio	4.3x optical
Viewing Angle Adjustment	Pan: 0°-350°, Tilt: 5°-175°, Rotate: 0°-350°
Lens Mount	Board mount
Horizontal Viewing Angle	109°-26.4°
Compression	H.264 High Profile, MJPEG
Maximum Frame Rate vs. Resolution	7 fps at 3648 x 2736 7 fps at 3648 x 2160 7 fps at 2592 x 1944 7 fps at 2048 x 1536 30 fps at 1920 x 1080 30 fps at 1280 x 720 30 fps at 640 x 480 15 fps at 320 x 240
Horizontal Resolution (TV lines)	1450 TVL
Multi-Streaming	Dual streams
Wide Dynamic Range	Basic WDR (70 dB)
Digital Noise Reduction	DNR
S/N Ratio	52 dB
Audio	2-way (Line-in, Line-out)
Network Protocol & Service	TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour
Pan, Tilt or Zoom protocol	Visca, Pelco-D, Pelco-P

Network Connector	RJ-45
Digital Input/Output	2/2
Local Storage	MicroSDHC/MicroSDXC memory card slot (card not included)
Power Source	PoE Class 2
Environmental Casing	Weatherproof (IP67); Vandal proof (IK10)
Bundled Accessories	No
Mount Type	Surface, Pendant, Wall, Corner, Pole, Flush, Gang Box
Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server)	Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection
Client PC Operating System	Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP
PC Web Browser	IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime
ONMF Compliant	Yes
Starting Temperature	-20°C ~ 50°C (-4°F ~ 122°F)
Operating Temperature	-40°C ~ 50°C (-40°F ~ 122°F)
Approvals	CE, FCC, IP67, IK10, NEMA4X
Warranty	3 Years
Product Availability	ACTi : 2014.11.21 Distributor : 2014.12.21
MSRP (local, reference only)	Log-in required