



	E910
Model	E910
Product Type	Mini Dome
Maximum Resolution	2MP
Application Environment	Outdoor
Image Sensor	Progressive Scan CMOS
Day / Night	No
Superior Low Light Sensitivity	Yes
Minimum Illumination	Color: 0.1 lux, B/W: 0.05 lux at F2.8
Mechanical IR Cut Filter	Yes
IR LED	No
Lens	Fixed focal, f1.9mm / F2.8, Fixed iris, Fixed focus
Viewing Angle Adjustment	Pan: $\pm 90^\circ$, Tilt: 0° - 90°
Lens Mount	Board mount
Horizontal Viewing Angle	109.49°
Compression	H.264 High Profile, MJPEG
Maximum Frame Rate vs. Resolution	60 fps at 1920 x 1080 60 fps at 1280 x 720 60 fps at 640 x 480 60 fps at 320 x 240
Horizontal Resolution (TV lines)	1450 TVL
Image Orientation	Rotation (0° , 90°)
Multi-Streaming	Dual streams
Wide Dynamic Range	Advanced WDR (145 dB)
Digital Noise Reduction	2D+3D DNR
Digital Image Stabilizer	Digital Image Stabilizer
S/N Ratio	52 dB
Audio	1-way (Mic-in, Line-in)
Network Protocol & Service	TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour
Network Connector	RJ-45
Digital Input/Output	No
Local Storage	MicroSDHC memory card slot (card not included)

Power Source	PoE Class 1
Environmental Casing	Weatherproof (IP68); Vandal proof (IK10); Vibration proof (EN50155-ready, without certificate)
Bundled Accessories	No
Mount Type	Surface, Gang Box
Built-in Analytics	Face Detection, Motion Detection, Tamper, People Counting
Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server)	Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection
Client PC Operating System	Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP
PC Web Browser	IE 8, IE 9, IE 10, IE 11, Firefox with V.L.C, Chrome with V.L.C, Safari with Quicktime
ONMF Compliant	Yes
Starting Temperature	-20°C ~ 50°C (-4°F ~ 122°F)
Operating Temperature	-20°C ~ 50°C (-4°F ~ 122°F)
Approvals	CE, FCC, IP68, IK10, NEMA4X, EN50155-ready (without certificate)
Warranty	3 Years
Product Availability	ACTi : 2015.01.23 Distributor : 2015.02.23
MSRP (local, reference only)	Log-in required