

| | E919M |
|-----------------------------------|---|
| Model | E919M |
| Product Type | Mni Fisheye Dome |
| Maximum Resolution | 3MP |
| Application Environment | Outdoor |
| Image Sensor | Progressive Scan CMOS |
| Day/Night | No |
| Superior Low Light Sensitivity | No |
| Mnimum Illumination | Color: 0.1 lux at F2.0 |
| Mechanical IR Cut Filter | No |
| IRLED | No |
| Lens | Fixed focal, f1.19mm / F2.0, Fixed iris, Fixed focus |
| Viewing Angle Adjustment | Rotate: ±90° |
| Lens Mount | Board mount |
| Horizontal Viewing Angle | 180° (overview area), 109.8° (high detail area) |
| Compression | H.264 High Profile, MPEG |
| Maximum Frame Rate vs. Resolution | 20 fps at 2048 x 1536 20 fps at 1440 x 1080 20 fps at 1280 x 960 20 fps at 800 x 600 15 fps at 640 x 480 15 fps at 320 x 240 |
| Horizontal Resolution (TV lines) | 1250 TVL |
| View Mode | Fisheye View |
| Multi-Streaming | Dual streams |
| Wide Dynamic Range | Superior WDR (110 dB) |
| Digital Noise Reduction | DNR |
| S/N Ratio | 52 dB |
| Network Protocol & Service | TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour |
| Network Connector | M12 |
| Digital Input/Output | No |
| Local Storage | MicroSDHC/MicroSDXC memory card slot (card not included) |
| Power Source | PoE Class 1 |
| | Whathammaf/ID69\-\ hadal amaf/IK10\- |

| Environmental Casing | vveauterproof (IPoo), vartual proof (IN 10), Vibration proof (EN50155) |
|--|--|
| Bundled Accessories | No |
| Mount Type | Surface, Gang Box |
| Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server) | Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection |
| Client PC Operating System | Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP |
| PC Web Browser | IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime |
| ONVIF Compliant | Yes |
| Starting Temperature | -20°C ~ 50°C (-4°F ~ 122°F) |
| Operating Temperature | -20°C ~ 50°C (-4°F ~ 122°F) |
| Approvals | CE, FCC, IP68, IK10, NEMA4X, EN50155 |
| Warranty | 3 Years |
| Product Availability | ACTi : 2014.08.08 Distributor : 2014.08.15 |
| MSRP (local, reference only) | <u>Log-in required</u> |