



	Q13
Model	Q13
Product Type	Fisheye Covert
Maximum Resolution	2MP
Application Environment	Indoor
Image Sensor	Progressive Scan CMOS
Day / Night	No
Superior Low Light Sensitivity	Yes
Minimum Illumination	Color: 0.1 lux at F2.0
Mechanical IR Cut Filter	No
IR LED	No
Lens	Fixed focal, f1.19mm / F2.0, Fixed iris, Fixed focus
Lens Mount	Board mount
Horizontal Viewing Angle	180°
Compression	H.264 High Profile, MJPEG
Maximum Frame Rate vs. Resolution	2MP
Horizontal Resolution (TV lines)	1100 TML
View Mode	Fisheye View
Multi-Streaming	Dual streams
Wide Dynamic Range	Basic WDR (75 dB)
Digital Noise Reduction	2D+3D DNR
S/N Ratio	52 dB
Audio	2-way (Line-in, Line-out)
Network Protocol & Service	TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour
Network Connector	RJ-45
Local Storage	MicroSDHC/MicroSDXC memory card slot (card not included)
Power Source	DC 12V; PoE Class 3
Environmental Casing	Vibration proof (EN50155)
Mount Type	Wall, Pendant, Flush
	Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter

Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server)	area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection
Client PC Operating System	Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP
PC Web Browser	IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime
ONMF Compliant	Yes
Starting Temperature	-20°C ~ 50°C (-4°F ~ 122°F)
Operating Temperature	-20°C ~ 50°C (-4°F ~ 122°F)
Approvals	CE, FCC, EN50155
Warranty	3 Years
Product Availability	ACTi : 2015.03.04 Distributor : 2015.04.04
MSRP (local, reference only)	